# Key Features

SuperColor: Amazing Color Accuracy | 3,600 Lumen

Brightness | Energy Efficient SuperEco | Reduced Input

Latency



## **Product Description**

The ViewSonic PA503X price-performance projector features 3,600 lumens, native XGA 1024 x 768 resolution, and intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. The PA503X also features extensive connectivity including HDMI, 2 x VGA, VGA out, Composite Video and audio in/out. An energy-saving SuperEco® feature reduces power consumption and extends the lamp life by up to 15,000 hours. With advanced audio-visual features, flexible connectivity options, and an affordable price, the PA503X is ideal for use in education and small business environments.







### Contact Sales

call: 888.881.8781

email:

salesinfo@viewsonic.com

visit: viewsonic.com

#### Display:

| Type:  | DLP   |
|--|---|
| Resolution Type:                                 | XGA   |
| Resolution:                                      | 1024 x 768                                      |
| Brightness (ANSI Lumens):                        | 3,500   |
| Throw Distance:                                  | 3.9 ft - 43 ft (100" @13 ft)                    |
| Throw Ratio:                                     | 1.96 ~ 2.15                                     |
| Display Size (in.):                              | 30 - 300 in. / 0.76 - 7.62 m                    |
| Keystone:  | Vertical (± 40°)                                |
| Lens:  | 1.1x Manual optical zoom / manual optical focus |
| Light Source (watt):                             | 190   |
| Light Source Life, Normal (hours):               | 4500  |
| Light Source Life, Dynamic Eco-<br>Mode (hours): | 15000   |
| Color Depth:                                     | 1.07B Color (R/G/B 10bit)                       |
| Dynamic Contrast Ratio:                          | 22000:1   |
| Aspect Ratio:                                    | 4:3   |
| Video Signal:                                    |   |
| Frequency Horizontal:                            | 15K~102KHz                                      |
| Frequency Vertical:                              | 23~120Hz  |
| Compatibility:                                   |   |

VGA (640 x 480) to WUXGA\_RB PC Resolution (max):

(1920 x 1200)

VGA (640 x 480) to WUXGA\_RB Mac® Resolution (max):

(1920 x 1200)

#### Connector:

Mini USB Type B(1), Audio Ouput (Mini Jack)(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4(1), VGA Out(1), Composite RCA Video In(1), RGB Input(2)

Audio:

Internal Speakers: 2W

Power:

AC 100-240V (universal), 50-60Hz Voltage:

Consumption (typical): 260W

Stand-by: <0.5W

Operating Conditions:

Temperature: 32-104° F (0-40° C)

Weight (imperial):

Net (lbs): 4.89

Gross (lbs): 7.14

Weight (metric):

Net (kg): 2.22

Gross (kg): 6.24

Dimensions (metric) (WxHxD):

Packaging (mm): 365 x 300 x 188

Copyright ©∑gewSosic Gorporation 2000-2017. All rights reserved. (06/29/2017 05:57 AM PST) Physical (mm):

Dimensions (imperial) (WxHxD):

Packaging (in.): 14.37 x 11.81 x 7.4

Physical (in.): 11.57 x 8.58 x 4.33

General:

Regulations: FCC (including ICES-003), cTUVus

PACKAGE CONTENTS: PA503X projector, power cable, VGA cable, remote control, Quick Start Guide, ViewSonic Wizard CD (with User

Warranty: 3-year limited warranty on parts and labor, 1st year free Express

Exchange® service\*\*

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907905113

Accessories: